

NISSAN DIESEL AMERICA, INC.

TECHNICAL BULLETIN EN-35 (Rev. B)

DATE: September 16, 2005
MODEL YEAR: ALL
ENGINE MODEL: J05 & J08
CHASSIS MODEL: UD1300 ~ UD3300
BULLETIN NUMBER: EN-35 (Rev. B - March 10, 2008)
FILE IN THE ENGINE SECTION OF THE TECHNICAL BULLETIN BINDER

UDXTRA ENGINE OIL

REVISION

This bulletin has been revised to include Operational Details for the "Type 1" & "Type 2" driving conditions.

PURPOSE

Genuine UDXtra Synthetic Blend 15W-40 Diesel Engine Oil for J05 & J08 engines is now available.



SERVICE INFORMATION

Oil change intervals should be based on the chart below, when using Genuine UDXtra Synthetic Blend Oil.

Vehicle Year/Model	Engine Model	Type 1 Condition Change Interval*	Type 2 Condition Change Interval*
2005~2007 UD1300~UD1800CS	J05	6 mo/ 9,000 miles**	6 mo/ 12,000 miles**
2005~2007 UD1800HD~UD3300	J08	6 mo/ 12,000 miles**	6 mo/ 20,000 miles**
2008~later UD1400~UD1800CS	J05	6 mo/ 8,000 miles**	6 mo/ 9,000 miles**
2008~later UD1800HD~UD3300	J08	6 mo/ 15,000 miles**	6 mo/ 20,000 miles**

* See Page #2 of this bulletin for an explanation of Type 1 and Type 2 conditions.
** Whichever comes first.

The extended engine oil change interval does not extend the other maintenance intervals, such as; chassis lubrication, fluid checks/adjustments etc. Dealers should refer their customers to the owners manual for all other service and maintenance recommendations.

Genuine UDXtra synthetic blend 15W-40 diesel engine oil has been approved for the J05 and J08 engines and has not been tested or approved for use in any other Nissan Diesel engine.

SERVICE INFORMATION (CONT.)

Refer to the tables below for explanations regarding “Type 1” & “Type 2” driving conditions.

Operational Details

Type 1 Conditions/	J08 Engines	Type 1 Conditions/ Operation	J05 Engines
	1) Off road usage		1) Off road usage
	2) Short haul / 80% city use		2) Short haul / 80% city use
	3) Heavy stop / start use		3) Heavy stop / start use
	4) Under 3,000 miles usage per month		4) Under 3,000 miles usage per month
Type 2 Conditions/	J08 Engines	Type 2 Conditions/ Operation	J05 Engines
	1) Long distance / 80% highway		1) Long distance / 90% highway
	2) Over 5,000 miles usage per month		2) Over 3,000 miles usage per month

Oil Requirement

Grade = API CJ-4
Genuine UD Xtra Engine Oil
SAE Viscosity = selected by temperature*

*See online Service Manual or Owner’s Manual for Correct SAE Viscosity.

THE INFORMATION CONTAINED IN THIS BULLETIN SHOULD NOT BE INTERPRETED AS THE BASIS FOR WARRANTY CLAIMS							
FOR THE INDICATED PERSONNEL BELOW, PLEASE READ, INITIAL, AND ROUTE TO THE FOLLOWING:							
X	SERVICE MANAGER	X	WARRANTY MANAGER	X SERVICE TECHNICIANS INITIAL BELOW:			
X	PARTS MANAGER	X	SHOP FOREMAN				