

Quon

CW 25 360
6x4 Rigid



QUON KEY FEATURES

SPECIFICATIONS

| | |
|----------------------|------------------------------------------------|
| Power: | 263 kW (357 PS) @ 2200 rpm |
| Torque: | 1428 Nm (1055 lb.ft) @ 1200 rpm |
| Transmission: | ESCOT-VI automated manual transmission (AMT) |
| Suspension: | Air bag suspension |
| Wheelbase: | 3700 mm (L-wheelbase) 5700 mm (V-wheelbase) |
| GVM: | 25,000 kg |
| GCM: | 38,000 kg |

UD TRUCKS EXTRA MILE SOLUTIONS



UD TRUCKS FINANCIAL SERVICES

Delivering flexible finance solutions that are tailored to your business. Helping to get your UD Quon on the road, as soon as possible.*



UD TRUCKS SERVICE AGREEMENTS

Peace of mind through tailored service plans, with fixed monthly costs and preventative maintenance options. Maximising fleet uptime and your bottom line.**



UD CONNECT

Keep track of your fleet, improve driver performance, save fuel and reduce maintenance costs, through our integrated telematics system with fully customisable reports.**



SMART FUEL EFFICIENCY AND RESPECT FOR THE ENVIRONMENT

GH8 engine: fuel efficient, powerful and clean.



SMART UPTIME

Quon has been designed to further optimise uptime, with superior reliability and increased maintenance intervals.



SMART SAFETY

Active safety with mechanical and electronic features throughout, including safety for vulnerable road users.



SMART PRODUCTIVITY

Light weight chassis helping to maximise payload.



SMART DRIVABILITY

The cabin has been designed with the user's comfort in mind, with outstanding ergonomics and visibility allowing the driver to concentrate on driving.


Going the Extra Mile.

*Finance offered by Volvo Financial Services Pty Ltd.

**Terms and conditions apply.

 **UD TRUCKS**

GENERAL SPECIFICATIONS

| SAFETY | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Passive Safety: | <ul style="list-style-type: none">Highly rigid cabin with ECE R29 ratingSide door beamsFront underrun protection system (FUPS)SRS driver steering wheel airbagDriver side seat belt with pre-tensionerSteering wheel & column with impact absorption function |
| Active Safety: | <ul style="list-style-type: none">Traffic Eye Brake System (AEB)Traffic Eye Cruise Control with auto stop & goTraffic sign recognitionLane departure warning systemElectronic stability controlAutomatic hill start assist (ESCOT VI)Lane change support LHS & RHSBlind spot information system LHS & RHSVulnerable road user detection LHS, RHS & front. |
| Basic Safety: | <ul style="list-style-type: none">LED Headlamps (low beam only)Disc brakesAnti Locking Brake SystemEmergency Braking SystemUD Extra Engine Braking (UD EEB)Safe Brake BlendingImmobiliserTwo-step entry and exit |
| ENGINE | |
| Model: | GH8F |
| Description: | 6 cylinder, 4 stroke diesel engine |
| Displacement: | 7,698 cc |
| Bore x stroke: | 110 mm x 135 mm |
| Compression ratio: | 17.5:1 |
| Max. Power (ECE Net): | 263 kW (357PS) @ 2,200 rpm |
| Max. Torque (ECE Net): | 1,428 Nm (1050lb.ft) @ 1,200rpm |
| Max. governed engine speed: |  |
| FUEL AND INTAKE SYSTEM | |
| Fuel capacity: | 400 litres |
| Injection type: | High pressure common rail direct fuel injection system |
| Filtration: | Chassis mounted primary filter and engine mounted secondary filter |
| EMISSION CONTROL | |
| Emission standard: | pPNLT (equivalent to Euro 6 emission requirements) |
| Adblue capacity: | 50 litres |
| Exhaust system: | RHS chassis mounted box muffler |
| ELECTRICAL | |
| Power: | 24 volt, negative ground system |
| Battery capacity: | 2 x 12 volt 135 Ah batteries |
| Alternator: | 110 amp |

| TRANSMISSION - ESCOT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-------|--|-----------------|-------|-----------------|------|-----------------|-------|-----------------|------|-----------------|------|-----------------|------|-----------------|------|------------------|------|-----------------|------|------------------|------|-----------------|------|------------------|------|-------|-------|-------|-------|
| Make: | UD Trucks | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Model: | ESCOT-VI (AT2612F) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Description: | Automated manual transmission (AMT) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Shift type: | 12 forward & 2 reverse gears | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Gear ratios: | <table><tr><td>1st</td><td>14.94</td><td>7th</td><td>3.44</td></tr><tr><td>2nd</td><td>11.73</td><td>8th</td><td>2.70</td></tr><tr><td>3rd</td><td>9.04</td><td>9th</td><td>2.08</td></tr><tr><td>4th</td><td>7.09</td><td>10th</td><td>1.63</td></tr><tr><td>5th</td><td>5.54</td><td>11th</td><td>1.27</td></tr><tr><td>6th</td><td>4.35</td><td>12th</td><td>1.00</td></tr><tr><td>Rev 1</td><td>17.48</td><td>Rev 2</td><td>13.73</td></tr></table> | | | | 1 st | 14.94 | 7 th | 3.44 | 2 nd | 11.73 | 8 th | 2.70 | 3 rd | 9.04 | 9 th | 2.08 | 4 th | 7.09 | 10 th | 1.63 | 5 th | 5.54 | 11 th | 1.27 | 6 th | 4.35 | 12 th | 1.00 | Rev 1 | 17.48 | Rev 2 | 13.73 |
| 1 st | 14.94 | 7 th | 3.44 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 nd | 11.73 | 8 th | 2.70 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 rd | 9.04 | 9 th | 2.08 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 th | 7.09 | 10 th | 1.63 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 th | 5.54 | 11 th | 1.27 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 th | 4.35 | 12 th | 1.00 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rev 1 | 17.48 | Rev 2 | 13.73 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PTO capability: | 1000 Nm @ 70% or 90% (PTR-D) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FRONT AXLE AND SUSPENSION SYSTEM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ground capacity: | 8,200 kg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Axle type: | Reverse Elliot I-Beam | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Suspension: | Parabolic leaf spring with shock absorbers | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Spring dimensions: | 90mm x 1460mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Spring constant: | 347.7 N/mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| REAR AXLE AND SUSPENSION SYSTEM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ground capacity: | 21, 000 kg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Axle type / model: | Single reduction, hypoid gear, with cross locks. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Final reduction ratio: | 3.78, 4.13, 4.50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LEAF SUSPENSION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Description: | Multi-leaf spring suspension, with rubber cushions | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Leaf dimensions: | 75mm x 1380mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AIR SUSPENSION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Description: | 8 air bag with shock absorbers | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Road friendly certification number: | RF2099 (air only) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Control system: | Electronic Controlled Air Suspension with remote control mounted in cab (ECAS4) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| BRAKES | |
|-----------------------------|---------------------------------------------------------------|
| Type: | Electronic braking system (EBS) with disc brakes on all axles |
| Front/Rear: | 430 mm rotors / 430 mm rotors |
| Park brakes: | Hand-operated pneumatic spring park brake on drive axles |
| Auxiliary brake: | Exhaust plus engine compression type (EEB) |
| Trailer connections: | Air and electrical connections to rear of chassis |

| STEERING | |
|-----------------------------|----------------------------------------------------|
| Type: | Recirculating ball and screw with hydraulic assist |
| Steering gear ratio: | 24.1 - 26.8 : 1 |
| Column: | Adjustable, tilt and telescopic control |
| Steering wheel: | 460 mm diameter with ignition key steering lock |

WHEELS & TYRES

| | |
|---------------------|---------------------------------------------------------------------------|
| Wheels: | 8.25in x 22.5in rim with 165mm offset and ISO 10 stud pattern (335mm PCD) |
| Front tyres: | 295/80 R22.5 Bridgestone R150Z |
| Rear tyres: | 11R 22.5 Bridgestone M711AZ |
| Spare tyre | 295/80 R22.5 Bridgestone R150Z |

FRAME

| | |
|------------------------------|----------------------------------|
| Width: | 850 mm |
| Side rail dimensions: | 300 mm x 90 mm x 7 mm |
| Material: | Rolled high tensile carbon steel |
| Tensile strength: | 600MPa / 600N/mm2 |

DRIVER INFORMATION & CUSTOMISABLE COLOUR DISPLAY SCREEN

| | |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In Dash Warning Systems: | Visual warning lamps with audible warning tones, plus written warnings displayed in full colour on the information screen |
| In Dash Driver Information: | Customisable live information includes: On board fuel coaching with economy tips, fuel & AdBlue usage, instant fuel consumption, digital speedo, trip computer including: time, distance & distance to empty. Hour meter, coolant temp, engine oil temp, transmission oil temp, UDPC level and volt meter. |

INTERNAL CABIN

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lighting: | Dual ON/OFF/DOOR interior lights Interior neon cabin lamp |
| Seating capacity: | Two (three seats optional) |
| Driver's seat: | ISRI 6860/875 air suspended seat with integrated seat belt & adjustable arm rest. Adjustable height control & rebound damper. With split seat back adjustments for recline & head rest position. Seat base tilt, seat cushion slide, seat air dump switch. Adjustable air bladders (4) for side bolsters, upper & lower lumbar. |
| Passenger seat/s: | Assistant seat with adjustable back & head rest |
| Sleeping capability: | ADR 42/04 compliant sleeper bunk with mattress and full curtains |
| Side windows: | Power operated door glass |
| Security: | Remote central locking with immobiliser |
| Air conditioning: | Fully automatic climate controlled air conditioning with recirculation filter |
| Multimedia unit: | <ul style="list-style-type: none"> ▫ 8-inch touch screen ▫ Hands-free Bluetooth operation. ▫ FM1, FM2, FM3, AM, DAB+ tuner ▫ USB input ▫ Up to 5 cameras input ▫ Wi -Fi Module ▫ Phone tethering ▫ Cordless Apple Car Play & Android Auto ▫ Truck specific satellite navigation ▫ OTA (over the air updates) |
| Storage: | Multiple in-cab compartments |
| Power Outlet: | 24 volt 240W & 12 volt 120W in dash |
| DIN accessory fitment: | Two DIN sized compartments |
| Floor covering | Vinyl |

EXTERNAL CABIN

| | |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cab Description: | Forward control, pressed steel construction |
| Mounting type: | Full floating, 4 bag air suspended cab with 4 dual acting shock absorbers and dual automatic height control valves. |
| Cab paint: | Standard – Polar White. Paint code W33 |
| Inspection points: | Back of the cab and front panel |
| Bumper type: | 3 piece with steel corner panels |
| Mirrors: | Heated and electrically operated main mirrors with flat glass, wide vision and passenger-side downward facing spot mirrors |
| Lamps: | <ul style="list-style-type: none"> ▫ LED head lamps (low beam) ▫ Bumper mounted fog lamps ▫ Roof mounted clearance lights |
| Wipers: | Triple arm, 2 speed wipers with variable intermittent operation and integrated washers |
| Reversing system: | Reverse beeper and digital infrared camera with microphone |

UD CONNECT (FLEET MANAGEMENT)

| | |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Telematics hardware: | In-cab GSM and GPS unit with SIMcard connected to roof antenna |
| Subscription: | First 12 months are complimentary with the purchase of a new UD Quon* |
| Key Reports: | <ul style="list-style-type: none"> ▫ Total operational time and distance ▫ Average speed and fuel consumption ▫ Total CO2 emission ▫ Vehicle utilisation ▫ Anticipating & braking ▫ Engine & gear utilisation ▫ Speed adaptation ▫ Time idling (standstill) |

FACTORY OPTIONAL EQUIPMENT

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Tyres: | 275 /70 R22.5 |
| Wheels: | Alcoa aluminium wheels |
| Rear engine PTO: | DIN 5462 or Flange SAE1410, 650 Nm capacity |
| Safety: | <ul style="list-style-type: none"> ▫ Driver Alert System ▫ Driver Monitor System |
| Cab paint: | Custom paint colours |
| Cab Interior: | Leather steering wheel, Woodgrain dash, Centre console or 2nd passenger seat |
| Cab Exterior: | Roof scoop, Chrome grille, Roof beacon prep kit, Bumper spoiler, passenger door peep window, cab auxiliary side windows |
| Additional Wheelbases: | 4,250mm 4,700mm 5,100mm |
| Chassis: | Additional 400 litre fuel tank (V wheelbase only), Front axle stabiliser bar |

MAJOR DIMENSIONS


| | Mass (kg) | | | | | | Vehicle Dimensions (mm) | | | | | | | | | | | | | | | |
|----------|----------------|-------|-------|------------|-----------|------------|-------------------------|------|-------|------|------|------|------|-----|------|------|------|------|-----|------|------|---------------|
| Variant | Wheelbase code | GVM* | GCM | Front Tare | Rear Tare | Total Tare | WB | TWB | OL | OW | OH | FT | RT | FW | AS | FOH | ROH | CA | GC | FHF | FHR | UD order code |
| UD - Air | L | | | 4050 | 3564 | 7615 | 3700 | 4385 | 8234 | | 2970 | | | | | | 2460 | 2985 | 201 | 1022 | 1029 | CW25360LAA |
| | V | 25000 | 38000 | 4002 | 3670 | 7672 | 5700 | 6385 | 11474 | 2490 | 2970 | 2044 | 1833 | 850 | 1370 | 1392 | 3610 | 4985 | 201 | 1027 | 1029 | CW25360VAA |
| | Z | | | 4456 | 3732 | 8188 | 6600 | 7285 | 11837 | | 2985 | | | | | | 3160 | 5885 | 200 | 1042 | 1058 | CW25360ZAA |

*Rated GVM and axle capacities are subject to Federal, State and Territory legal requirements.

Mass is an estimation based only on standard model, includes fluids (no diesel fuel or Adblue®). Excludes spare wheel. Excludes driver and tools. Subject to ± 3% tolerance.

Ground clearance is based on vehicle with standard wheels and tyres
For alloy rims deduct 28kg from Front tare and deduct 56kg from each rear axle in rear tare.

For alloy rims add 18mm to both FT and RT measurements



WARRANTY

- Standard warranty*

36 months/500,000 kms
- Cab corrosion warranty*

36 months/unlimited kms

+ For details refer to your UD Trucks New Vehicle Warranty brochure
++ Purchased by the owner and covers selected factory items only.
For details refer to your UD Trucks New Vehicle Warranty brochure

TAKE YOUR BUSINESS FURTHER
WITH UD TRUCKS EXTRA MILE SOLUTIONS



UD TRUCKS FINANCIAL SERVICES
Fast, competitive, customisable and fuss-free

UD Trucks Financial Services deliver professional and customisable solutions directly through your UD Trucks dealer network. You'll get a comprehensive and flexible finance solution that's tailored to your needs. We will help to get your UD Truck on the road, as soon as possible.*

- ✓

Fast and easy to work with
We are easy to do business with, and you can depend on us to secure a competitive and fast finance package.
- ✓

Tailored Solutions
We take the time to get to know you and your business so that we can offer you the best tailored solution. One that meets your needs and is flexible enough to carry you confidently into the future.
- ✓

A second financing source
Your bank credit line is best used as a cash flow buffer to your daily activities. That's why having a second line of credit from UD Trucks Financial Services is a more effective way to finance your truck purchase.



UD TRUCKS SERVICE AGREEMENTS
Complete peace of mind

Managing a fleet is no easy task, but with UD Trucks Service Agreements, we can make that much simpler while maximising uptime and providing full peace of mind.

Not only will your fleet enjoy professional service and high-quality, assured parts from UD Trucks, you can also have improved cost control with our simple, fixed monthly invoicing and help from our service advisers every step of the way.**



UD TRUST ULTIMATE
The UD Trust Ultimate plan is the most comprehensive of all the UD Trucks Service Agreements. with the added confidence of repairs to the electrical, engine, driveline, braking and steering systems.



UD TRUST EXTRA
The UD Trust Extra plan covers all that is included in the Standard Program as well as repairs to the driveline components, brakes and clutch components.



UD TRUST STANDARD
The UD Trust Standard plan is designed to service your vehicle in line with your customised OEM backed service plan, giving your vehicle the right maintenance to go the Extra Mile.



UD CONNECT
Keeping your fleet in check

UD Connect uses advanced telematics technology to capture data on operational and truck performance. Providing easy-to-read reports to inform you and then take steps to improve driver performance, save fuel and reduce maintenance costs. Monitoring driver and truck performance, with real-time analysis and top-line reporting.

Each UD Truck in Australia that's fitted with UD Connect and that has been signed up to our agreement, will give you instant feedback on driver behaviour while they're out on the road, allowing you to identify areas of improvement.***

- ✓

Keeping track of your fleet
Provides important information about your UD fleet so that you know where your trucks are at all times and can track the status of your deliveries.
- ✓

Helping to reduce fuel consumption
Easy to read reports on fuel usage and driver behaviour, so that you can optimise your fuel consumption and improve your bottom line.
- ✓

Maximising fleet uptime
Comprehensive and proactive support to assist fleet uptime and productivity.