Condor

PD 26 300

Model	PD 26 300
Power	221kw (300ps) @ 2,200rpm
Torque	984Nm @ 1,000rpm
Transmission	Allison 3,500 Series
GVM	26,000kg

Safety	
Passive Safety	• R29 Cabin • Front underrun protection system (FUPS) • SRS Airbag (Driver & Passenger) • Driver side belt in seat
Active Safety	• Lane Departure Warning System (LDWS) • Forward Vehicle Start Notification (FVSN) • Advanced Emergency Braking System (AEBS)* • Distance Warning System • Full Speed Range Adaptive Cruise Control • Electronic Vehicle Stability Control (ESC) *Forward Vehicle Detection only
Basic Safety	• Full LED Headlights • Disc brakes w/ wear indicator

Engine	
Model	DB6A-TCC
Description	6 Cylinder Turbo Diesel, Intercooler
Displacement	6,690 cc
Max. Power	221kw (300ps) @ 2,200rpm
Max. Torque	984Nm @ 1,000rpm

Fuel and Intake System	
Fuel capacity	400L Std (Aluminium)

Emission Control	
Emission standard	Euro 6 - C
AdBlue capacity	65L
Exhaust system	RHS chassis mounted box muffler

Electrical	
Power	24V
Battery capacity	115E41L
Alternator	90 Amp

Transmission		
Make	Allison 3,500 Series	
Model	MD3560	
Description	6 speed fully automatic	
Shift type	Push button shift selector	
Gear Ratios	1st	4.593
	2nd	2.257
	3rd	1.535
	4th	1.000
	5th	0.749
	6th	0.651
	REV	4.999

Front Axle and Suspension System	
Ground capacity	7,300kg

Rear Axle and Suspension System	
Ground capacity	19,000kg

Brakes	
Type	Brake Disc with Brake Pad Wear Indicator
Auxiliary brake	Engine Retarder (Compression Release Engine Brake)

Steering	
Column	Adjustable, tilt and telescopic control
Steering wheel	440mm diameter

Wheels & Tyres	
Front tyres	315/70 R22.5 - 156/150L Michelin X MULTI ENERGY Z2
Rear tyres	11R22.5 148/145L Michelin X MULTI D+
Spare tyre	315/70 R22.5 - 156/150L Michelin X MULTI ENERGY Z2
Wheels	STL (Steel) or ALM (Alumnium)

Major Dimensions	
Model	**PD26300WAA**
Suspension	Air
Wheelbase code	W
GVM	26000
Front Tare	3683
Rear Tare	3387
Total Tare	7070
Wheelbase	5970
Theoretical Wheelbase	6655
Overall Length	11336
Overall Width	2485
Overall Height	3000
Front Track	2045
Rear Track	1840
Frame Width	870
Axle Spread	1370
Front Overhang	1255
Rear Overhang	3426
Rear Frame Length	2741
Cab to Axle	6529

Frame	
Width	870mm
Side rail dimensions	305mm x 90mm x 8mm

Internal Cabin	
Seating capacity	3
Driver's seat	Premium ISRI Seat
Passenger seat	Full flat passenger seat
Sleeping capability	ADR 42/05 compliant sleeper bunk
Side windows	Power operated door glass
Security	Remote central locking with immobiliser
Air conditioning	Auto Climate Control Air Conditioner
Storage	• Centre Console • Pull out cup holder
Power outlet	1x 12V Accessory Socket, 1x USB
DIN accessory fitment	Two DIN sized compartments
Floor covering	Vinyl

External Cabin	
Cab paint	Arc White
Mirrors	Heated and electrically operated main mirrors with flat glass, wide vision and passenger-side downward facing spot mirror
Lamps	• LED Day Running Light • LED Turn Signal Light (Front) • LED Adaptive Drive Beam Headlight (ADB) • LED Fog Light • LED Turn Signal Light (Side) • Halogen Cornering Light
Wipers	Triple arm, variable intermittent operation and integrated washers

Warranty Information	
Standard Warranty*	72 Months / 500,000km / 8,000hrs
Severe Application Warranty*	36 Months / 200,000km / 8,000hrs

*Tare Weight note using Steel Rims (excl fuel, driver; including tools, spare wheel). Specifications and details are subject to change. *Whichever occurs first - months/kilometers/hours. " DISCLAIMER: Imported and distributed by Volvo Group Australia Pty Ltd (ABN: 27 000 761 259). Images for illustration purposes. Volvo Group Australia Pty Ltd reserves the right to modify design and change equipment without previous notification. Please consult with your UD Trucks Dealer for the latest information about vehicle specifications. Last published: November 2025"*