

TECHNICAL BULLETIN # GE - 20

DATE: FEBRUARY 2, 2000 **MODEL YEAR:** 1999 AND AFTER **CHASSIS MODEL:** UD1800HD ~ UD3300


BULLETIN #: GE - 20

FILE IN THE GENERAL SECTION OF THE TECHNICAL BULLETIN BINDER

FEGTA FUEL INJECTION NOZZLE OPENING PRESSURE CORRECTION

CORRECTION NOTICE

The UD Truck Service Manual CD contains discrepencies in the fuel injection nozzle opening pressure for the 1999 model year and after UD1800HD ~ UD3300. The correct fuel injection nozzle opening pressures are provided below for the indicated pages of the UD Truck Service Manual CD. Adjust the fuel injection nozzle to the opening pressure described below as conditions require:



• Page EF-1-1 (CD Page 265)

SERVICE DATA SPECIFICATIONS

Fuel injection nozzle; Injection pressure	20,098 ~ 21,078	205 ~ 215	2,914 ~ 3,056
	kPa	kgf/cm ²	psi

• Page EF-1-3 (CD Page 267)

SERVICE DATA

Nozzle; Injection starting pressure	20,098 ~ 21,078	205 ~ 215	2,914 ~ 3,056
	kPa	kgf/cm ²	psi

• Page EF-4-3 (CD Page 286)

ADJUSTMENT

Fuel injection pressure	20,098 ~ 21,078	205 ~ 215	2,914 ~ 3,056
	kPa	kaf/cm²	psi