

NISSAN DIESEL AMERICA, INC.

TECHNICAL BULLETIN TR-24

DATE: December 22, 2006
 MODEL YEAR: 2006 & LATER
 TRANSMISSION: ALLISON
 CHASSIS MODEL: 1800HD ~ 3300
 BULLETIN NUMBER: TR-24
FILE IN THE TRANSMISSION SECTION OF THE TECHNICAL BULLETIN BINDER

ALLISON TRANSYND™ & DEXRON® III FLUID CHANGE INTERVAL

PURPOSE

To advise the UD Truck dealer network that the scheduled service interval for the Allison *TranSynd*™/TES 295 approved fluids has changed.

RECOMMENDED SERVICE INTERVAL

The online service maintenance schedule has been updated to reflect these changes.

Vehicle Model	Trans Type	Service Interval	Fluid Specification
1800HD - 3300	Allison ATM**	24 months / 50,000 miles*	Dexron® III
1800HD - 3300	Allison ATM***	48 months /150,000 miles*	<i>TranSynd</i> ™/TES 295

*which ever comes first
** 2005MY & prior have factory fill Dexron® III
***2006MY & later have factory fill <i>TranSynd</i> ™ fluid

TranSynd™/ TES295 cannot be mixed with any Dexron® III fluid or damage to the transmission will result.

THE INFORMATION CONTAINED IN THIS BULLETIN SHOULD NOT BE INTERPRETED AS THE BASIS FOR WARRANTY CLAIMS							
FOR THE INDICATED PERSONNEL BELOW, PLEASE READ, INITIAL, AND ROUTE TO THE FOLLOWING:							
X	SERVICE MANAGER	X	WARRANTY MANAGER	X SERVICE TECHNICIANS INITIAL BELOW:			
X	PARTS MANAGER	X	SHOP FOREMAN				